

Flextek Lite

PREMIUM STRIP LIGHT
 SELV 48V VERSION

KEY FEATURES

- > 7-Years Warranty
- > AC/DC IC Solution
- > Brilliant Brightness
- > High Temperature Operation
- > Customize Length and Output
- > Over Voltage Protection

TECHNICAL SPECIFICATIONS

WARRANTY	7 Years		SDCM	<5
RATED LIFETIME	≥70,000 hours		OPERATING TEMP.	-30°C ~ +60°C
IP / IK RATINGS	IP67 / IK10		CONNECTION	IP68 Connector
MATERIAL	Food Grade Silicon / Transparent		DIMENSION	L x 14 (W) x 5 (H) mm
CRI	≥80		CCT	4000K / 5700K
MODEL	FL-4-48-L	FL-6-48-L	FL-8-48-L	FL-10-48-L
LED POWER	3.84 W/m	5.76 W/m	7.68 W/m	9.6 W/m
LUMEN OUTPUT	427 lm/m	640 lm/m	937 lm/m	1274 lm/m
SINGLE DISTANCE	70m	55m	45m	35m
PCB	2oz	2oz	2oz	2oz
MODEL	FL-4-48-H	FL-6-48-H	FL-8-48-H	FL-10-48-H
LED POWER	3.84 W/m	5.76 W/m	7.68 W/m	9.6 W/m
LUMEN OUTPUT	427 lm/m	640 lm/m	937 lm/m	1274 lm/m
SINGLE DISTANCE	100m	80m	65m	50m
PCB	4oz	4oz	4oz	4oz
DRIVER MODEL	DL-750W-V48-EXS	UHP-1000-48		
Max. POWER	750W	1000W	PROTECTION	Over Voltage/Temperature Protection
INPUT VOLTAGE	100-277VAC	90-264VAC	FEATURES	Non-Flickering Design
OUTPUT VOTLAGE	48VDC	48VDC	WARRANTY	5-Years
DIMENSION	237x100x40m	240x115x41m	CERTIFICATION	CE/RoHS