

Flextek Pro

INDUSTRIAL GRADE STRIP LIGHT
SELV 48V VERSION

KEY FEATURES

- > 10-Years Warranty
- > AC/DC IC Solution
- > Brilliant Brightness
- > High Temperature Operation
- > Customize Length and Output
- > Over Voltage Protection



TECHNICAL SPECIFICATIONS					
WARRANTY	10 Years		SDCM	<5	
RATED LIFETIME	≥100,000 hours		OPERATING TEMP.	-30°C ~ +65°C	
IP / IK RATINGS	IP67 / IK10		CONNECTION	IP68 Connector	
MATERIAL	Food Grade Silicon / Transparent		DIMENSION	L x 22 (W) x 7 (H) mm	
CRI	≥80		CCT	4000K / 5700K	
MODEL	FP-3-48-L	FP-4-48-L	FP-6-48-L	FP-7-48-L	FP-9-48-L
LED POWER	2.88 W/m	4.32 W/m	5.76 W/m	7.2 W/m	8.64 W/m
LUMEN OUTPUT	317 lm/m	448 lm/m	705 lm/m	959 lm/m	1274 lm/m
SINGLE DISTANCE	100m	80m	65m	55m	45m
PCB	2oz	2oz	2oz	2oz	2oz
MODEL	FP-3-48-H	FP-4-48-H	FP-6-48-H	FP-7-48-H	FP-9-48-H
LED POWER	2.88 W/m	4.32 W/m	5.76 W/m	7.2 W/m	8.64 W/m
LUMEN OUTPUT	317 lm/m	448 lm/m	705 lm/m	959 lm/m	1274 lm/m
SINGLE DISTANCE	145m	115m	95m	75m	60m
PCB	4oz	4oz	4oz	4oz	4oz
MODEL	FP-3-48-E	FP-4-48-E	FP-6-48-E	FP-7-48-E	FP-9-48-E
LED POWER	2.88 W/m	4.32 W/m	5.76 W/m	7.2 W/m	8.64 W/m
LUMEN OUTPUT	317 lm/m	448 lm/m	705 lm/m	959 lm/m	1274 lm/m
SINGLE DISTANCE	200m	160m	130m	100m	80m
PCB	8oz	8oz	8oz	8oz	8oz
DRIVER MODEL	DL-750W-V48-EXS		UHP-1000-48		
Max. POWER	750W		1000W	PROTECTION	Over Voltage/Temperature Protection
INPUT VOLTAGE	100-277VAC		90-264VAC	FEATURES	Non-Flickering Design
OUTPUT VOTLAGE	48VDC		48VDC	WARRANTY	5-Years
DIMENSION	237x100x40m		240x115x41m	CERTIFICATION	CE/RoHS