



# WE HELP YOU WITH PROFESSIONAL

Formed in 2008, marketing leading LED solution with end-to-end capabilities. Your reliable LED products partner for any projects with superior and reliable quality up to 10 years warranty.

Follow us and discover more



# WHO WE ARE ?

Internationally-renowned lighting solutions provider and manufacturer

TLG is an Australian based lighting group founded on the principles of quality, innovation and a strong customer focus. Vertically integrated from product development and design to manufacturing and distribution, with projects in over 40 countries across Asia Pacific, Europe, North America and the Middle East.

**LUMAN** + **TEKNIK** = **TLG** | TEKNIK LUMAN GROUP  
> illuminating the greens LIGHTING SOLUTIONS

## WHY CHOOSE US ? WE SPECIALIZE IN

- ✓ R & D | Manufacturing
- ✓ Excellent Quality Management
- ✓ Global Knowledge and Experience
- ✓ Professional Marketing Team With Effective Brand Support

## FLEXTEK PRO

Premium Flexible Rope Light With Market-Leading Features

**MAX**  
**6000**  
LUMEN/  
PER METER

Highest output  
in the market



**NON**  
FLICKERING

PROFESSIONAL  
**IC**  
CONTROLLED

**65°C**  
Max. Ta

  
**>30KG**  
TENSILE  
STRESS

**5**  
YEAR  
PRODUCT  
WARRANTY

**IP**  
**67**  
INGRESS  
PROTECTION

**IK**  
**10**  
IMPACT  
PROTECTION



# FlexTEK Pro

PREMIUM STRIP LIGHT  
 110VDC VERSION

## KEY FEATURES

- > 10-Years Warranty
- > Onsemi IC Solution
- > Brilliant Brightness By 200lm/w
- > High Temperature Operation Ta65°C
- > Customize Length and Output
- > Single Run >125m No Light Drops



## TECHNICAL SPECIFICATIONS

<b>WARRANTY</b>	10 Years	<b>SDCM</b>	<5
<b>RATED LIFETIME</b>	≥70,000 hours	<b>OPERATING TEMP.</b>	-30°C ~ +65°C
<b>IP / IK RATINGS</b>	IP67 / IK10	<b>INPUT VOLTAGE</b>	110VDC
<b>MATERIAL</b>	Silicon	<b>FIRE RATING</b>	UL94-V0
<b>CRI</b>	≥80	<b>INSTALLATION</b>	Surface Mount
<b>MODEL</b>	<b>FP-14D</b>		
<b>POWER</b>	10 W/m		
<b>LUMEN OUTPUT</b>	2000 lm/m		
<b>EFFICACY</b>	200 lm/W		
<b>CCT</b>	4000K/5700K		
<b>OPTICS</b>	120°		
<b>DIMMABLE</b>	Non-Dim		
<b>DIMENSIONS</b>	L x 22 (W) x 7 (H) mm		
<b>COLOUR</b>	Transparent		
<b>Max. Length</b>	125m Single Run		